

PATENT  
450100-03140

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

TITLE: SPECIAL EFFECT IMAGE GENERATING  
APPARATUS

INVENTOR: Masafumi KURASHIGE

William S. Frommer  
Registration No. 25,506  
FROMMER LAWRENCE & HAUG LLP  
745 Fifth Avenue  
New York, New York 10151  
Tel. (212) 588-0800

SPECIAL EFFECT IMAGE GENERATING APPARATUS

## BACKGROUND OF THE INVENTION

## 5           1.    Field of the Invention

The present invention relates to a special effect image generating apparatus for processing an image to generate a special effect.

## 10           2.    Description of the Related Art

Processing original data for an image to give it a unique visual effect is a common practice in preparing television broadcast images and various other various. The types of image processing include

15   "posterization" and "solarization" for reducing the number of gradients of the image data, "mosaic" processing for dividing an image to blocks of uniform densities, "mono" processing for making an image monochrome, "contrast" processing for adjusting the

20   luminance difference of an image, and other various types of processing.

The special effect image generating apparatus of the related art performs the above variety of processing on an image as selected in an image conversion

25   processing circuit. When doing this, it generates a mask

pattern from a mask pattern generator to mask regions of the image not to be processed and used this mask pattern so as to process only predetermined regions of the image.

In the above special effect image generating apparatus of the related art, since predetermined positions of the image input to the apparatus were masked regardless of the state of the input image, when for example performing mosaic processing, the operator had to control the mask conditions to deal with any movement of the portions of the image to be masked accompanying movement of the input image. This adjusting operation required a lot of work.

#### SUMMARY OF THE INVENTION

An object of the present invention is to provide a special effect image generating apparatus capable of processing an input image based on luminance information and color information with a high accuracy while suitably handling even movement of the image and without imposing any burden on an operator in an adjusting operation so as to generate a special effect giving visually unique luminance and color effects.

To attain the above object, according to the present invention, there is provided a special effect image generation apparatus for processing an image to generate

extracting from the above image an image satisfying a

5 plurality of extraction conditions among luminance  
extraction conditions based on a luminance signal and/or  
chroma extraction conditions based on at least a color  
signal; a key signal output means for outputting a key  
signal for setting extraction conditions for the image  
10 based on the luminance extraction conditions and/or the  
chroma extraction conditions; and a mixer circuit for  
processing the image to convert the image to a special  
effect image based on a signal of the image, an output  
signal of the image conversion means, and the key signal.

15            Preferably, the special effect image generation  
apparatus further comprises a mask pattern generation  
means for outputting a mask pattern for masking a region  
not to be processed in the image, and  
the key signal output means outputs a key signal to set  
20 the extraction conditions for the image based on the mask  
pattern in addition to the luminance extraction  
conditions and/or chroma extraction conditions.

Alternately, the special effect image generation apparatus further comprises an image conversion setting  
25 and processing means for selecting and setting a type of

image conversion to be performed on the image and making  
the image conversion means perform the selected and set  
image conversion on the image; and the selection and  
setting of the type of image conversion in the image  
5 conversion setting and processing means and the setting  
of the luminance extraction conditions and/or chroma  
extraction conditions are freely and independently  
performed.

More preferably, the special effect image generation  
10 apparatus further comprises a mask pattern generation  
means for outputting a mask pattern to mask a region not  
to be processed in the image; the key signal output means  
outputs a key signal for setting the extraction  
conditions for the image based on the mask pattern in  
15 addition to the luminance extraction conditions and/or  
chroma extraction conditions; and the setting and  
adjustment of the mask pattern generated by the mask  
pattern generation means, the selection and setting of  
the type of image conversion in the image conversion  
20 setting and processing means, and the setting of the  
luminance extraction conditions and/or chroma extraction  
conditions are freely and independently performed.

Alternatively, the special effect image generation  
apparatus further comprises a wave-filtering and shaping  
25 means for filtering and shaping the output signal of the

extraction condition setting means.

Preferably, the image conversion means reduces the number of gradients of data of the image.

Alternatively, the image conversion means divides  
5 the image into blocks of uniform density.

Preferably, the chroma extraction conditions are extraction conditions based on a luminance signal and color difference signal of the image.

Alternatively, the chroma extraction conditions are  
10 decided for a two-dimensional region of a color difference value defined by a color difference signal of blue and luminance and a color difference signal of red and luminance of the image.

More preferably, the chroma extraction conditions  
15 are decided for a three-dimensional region of a color difference value and a luminance value defined by a color difference of a two-dimensional region of the color difference signal and a luminance value at a predetermined position in the two-dimensional region.

20 Preferably, the extraction condition setting means extracts an image based on an NAM output of the luminance extraction conditions and/or the chroma extraction conditions.

These and other objects and features of the present invention will become clearer from the following description of the preferred embodiments given with reference to the attached drawings, in which:

5        Fig. 1 is a block diagram of the configuration of a key portion of an embodiment of the present invention;

      Fig. 2 is a block diagram of the overall configuration of an embodiment of the present invention;

      Figs. 3A to 3D are views for explaining preparation  
10      of a key signal corresponding to the luminance of an input image of an embodiment of the present invention;

      Figs. 4A and 4B are views for explaining preparation  
of a key signal corresponding to regions having a  
reference luminance or more or a reference luminance or  
15      less in the input image of an embodiment of the present invention;

      Figs. 5A to 5C are views for explaining preparation  
of a key signal corresponding to a predetermined range of  
a luminance region of the input image of an embodiment of  
20      the present invention; and

      Figs. 6A and 6B are views for explaining preparation  
of a key signal corresponding to a color signal of an  
input image of an embodiment of the present invention.

Below, preferred embodiments of the present invention will be explained with reference to Figs. 1 to 6.

Figure 1 is a block diagram of the configuration of a key portion of the present embodiment, Fig. 2 is a block diagram of the overall configuration of the present embodiment, Figs. 3A to 3D are views for explaining preparation of a key signal corresponding to luminance of an input image of the present embodiment, Figs. 4A and 4B are views for explaining preparation of a key signal corresponding to regions having a reference luminance or more or a reference luminance or less in the input image of the present embodiment, Figs. 5A to 5C are views for explaining preparation of a key signal corresponding to a predetermined range of a luminance region of the input image of the present embodiment, and Figs. 6A and 6B are views for explaining preparation of a key signal corresponding to a color signal of an input image of the present embodiment.

In the present embodiment, as shown in Fig. 2, a control panel 20 is provided to enable an operator to input a variety of operation signals, a system CPU 21 for controlling the overall operation is connected to the control panel 20, and a pre video modification unit 23 is connected to the system CPU 21. The pre video



modification unit 23 comprises, as shown in Fig. 1, an  
image conversion processing circuit 1 for performing  
"posterization" for reducing the number of gradients of  
luminance data of an image, "solarization" for reducing  
5 the number of gradients on color data of the image,  
"mono" processing for making the image monochrome,  
"contrast" processing for adjusting luminance differences  
of the image, etc., a luminance and chroma condition  
setting circuit 7 for extracting an image satisfying  
10 luminance extraction conditions set in the image and  
chroma extraction conditions, and a mask pattern  
generator 14 for outputting a mask pattern for masking a  
region not to be processed in the image.

Also, the system CPU 21 is connected to an address  
15 generator 22 which outputs a corresponding address at the  
time of enlargement and/or reduction, movement, and page  
turning of the image. The address generator 22 is  
connected to a transformation unit 24 for performing the  
above enlargement and/or reduction. An input terminal of  
20 the transformation unit 24 is connected to an output  
terminal of the above pre video modification unit 23.  
Furthermore, the transformation unit 24 is provided with  
a mapping memory used in the enlargement and/or reduction  
and an anti-alias filter for removing jags generated at  
25 oblique lines in the image along with the enlargement

and/or reduction.

Similarly, the system CPU 21 is connected to a post video modification unit 25. An input terminal of the post modification unit 25 is connected to an output terminal of the above transformation unit 24. The post video modification unit 25 has the functions of adding to an output signal of the transformation unit 24 a tail shaped moving locus or a star shaped moving locus at the time of moving an image and adding a background to an image according to a selecting operation by the operator.

The key portion of the pre video modification unit 32 of the present embodiment is configured as shown in Fig. 1 and comprises an image conversion processing circuit 1 for performing "posterization" for reducing the number of gradients on luminance data of an image, "solarization" for reducing the number of gradients on color data of the image, "mosaic" processing for dividing an image to blocks of uniform density, "mono" processing for making the image monochrome, "contrast" processing for adjusting luminance differences of the image, etc., a delay circuit 3 for delaying an input image signal, and a key signal generator 15 for outputting a key signal for processing the input image connected in parallel to an input terminal "ti". An output terminal of the image conversion processing circuit 1 is connected to the delay

circuit 2, an output terminal of the delay circuit 2 is connected to a first input terminal of a mixer circuit 5, an output terminal of the delay circuit 3 is connected to a second input terminal of the mixer circuit 5, and an output terminal of the key signal generator 15 is connected to a third input terminal of the mixer circuit 5 via a switch 13 and a delay circuit 6. The mixer circuit 5 has a function of preparing a special effect image and outputting a corresponding special effect image signal based on an output signal of the delay circuit 2, an output signal of the delay circuit 3, and an output signal of the delay circuit 6.

The above key signal generator 15 is provided with a luminance and chroma condition setting circuit 7 for extracting and outputting an image portion corresponding to luminance and chroma conditions set by the operator based on the luminance and colors of the image from the input image. The input terminal ti of the image signal is connected to an input terminal of the luminance and chroma condition setting circuit 7. The luminance and chroma condition setting circuit 7 comprises a plurality of lumi-key setting circuits 16a to 16m set with extraction luminance conditions based on the luminance of the image and a plurality of chroma key setting circuits 18a to 18n set with extraction chroma conditions based on

the luminance and colors connected in parallel to the input terminal "ti". The lumi-key setting circuits 16a to 16m are respectively connected to inversion circuits 17a to 17m, while the chroma key setting circuits 18a to 18n are respectively connected to inversion circuits 19a to 19n. When the levels of the input signals overlap, the output terminals of the inversion circuits 17a to 17m and 19a to 19n are connected to a NAM circuit 9 for selecting a signal of the higher level and outputting the same. An output terminal 9 of the NAM circuit 9 becomes an output terminal of the luminance and chroma condition setting circuit 7.

In the key signal generator 15, the output terminal of the luminance and chroma condition setting circuit 7 is connected to a wave-filtering and shaping circuit 8 for two-dimensional low pass filtering and signal shaping. The output terminal of the wave-filtering and shaping circuit 8 is connected to the inversion circuit 10 via a switch 11. Furthermore, an output terminal of the inversion circuit 10 is connected to a mask processing circuit 12, while the mask processing circuit 12 is connected to a mask pattern generator 14 for outputting a desired mask pattern signal by operation by the operator. The mask processing circuit 12 has a function of masking an output signal from the luminance

and chroma condition setting circuit 7 to be processed in the wave-filtering and shaping circuit 8 by a mask pattern signal from the mask pattern generator 14. An output terminal of the mask processing circuit 12 is  
5 connected to a delay circuit 6 via a switch 13, while an output terminal of the delay circuit 6 is connected to the third input terminal of the mixer circuit 5.

The operation of the present embodiment configured in this way will be explained next. The operator inputs  
10 from the control panel 20 the instruction operation signal necessary for the processing of the image. The instruction operation signal includes an image conversion instruction for selecting image conversion processing of "posterization" for reducing the number of gradients in  
15 luminance data of an image of the image conversion processing circuit 1 of the pre video modification unit 23, "solarization" for reducing the number of gradients in color data of the image, "mosaic" processing for dividing an image into blocks of uniform density,  
20 "mono" processing for making the image monochrome, "contrast" processing for adjusting luminance differences of the image, etc. Further, the instruction operation signal includes a luminance and chroma condition instruction of the luminance and chroma condition setting  
25 circuit 7 and a mask instruction for instructing a shape

and position of a mask pattern to be generated by the mask pattern generator 14. Furthermore, the instruction operation signal input from the control panel 20 includes, if required, an image transformation instruction for enlarging, reducing, moving, and rotating a designated portion of an image by selection by the operator.

Here, the luminance and chroma condition instruction of the luminance and chroma condition setting circuit 7 entered by the operator will be explained. First, the setting of a lumi-key for deciding the extraction luminance conditions based on the luminance of the image will be explained. The extraction luminance conditions are set based on the luminance of the image in this case by the operator operating a level setting device provided on the control panel 20 and having a display panel displaying a luminance range (0 to 10) of the image.

Figure 3A is a view of the relationship between a luminance level  $L$  of the input image signal of the image and time " $t$ ", wherein a key signal  $Fk3$  shown in Fig. 3D is output as a key signal for extracting from the input image signal an image having a luminance level of a predetermined level  $L4$  or more set in advance. In this case, as shown in Fig. 4A, an output level signal "Out" is found by multiplying an amplification constant "gain"

with a difference of a luminance level signal "in" of the input image and an upper limit reference value "clip". A key signal Fk3 as shown in Fig. 3D can be obtained by a limiter circuit making the output level signal "Out" zero  
5 when "Out"<0 and making "Out" 1.0 when "Out">1.0.

Also, a key signal Fk1 shown in Fig. 3B is output as a key signal for extracting from the input image signal an image having a luminance level of a predetermined level L1 or less set in advance. In this case, as shown  
10 in Fig. 4B, an output level signal "Out is found by multiplying an amplification constant "gain" with a difference of a luminance level signal "in" of the input image and a lower limit reference value "min". A key signal Fk1 as shown in Fig. 3B can be obtained by a  
15 limiter circuit making the output level signal "Out" 0 when "Out"<0 and making "Out" 1.0 when "Out">1.0.

As a key signal for extracting from the input image signal an image of a luminance level of a predetermined level range ( $L2 < L < L3$ ) set in advance, a key signal Fk2  
20 shown in Fig. 3C is output. In this case, a central value "center" of the upper limit value L3 (clip) and the lower limit value L2 (min) is obtained as shown in Fig. 5A. An absolute value "ABS" of the difference of the luminance level signal "in" of the input image and "center" is  
25 calculated as shown in Fig. 5B. Furthermore, as shown in

Fig. 5C, the absolute value "ABS" of the difference of the luminance level signal "in" of the input image and "center" is subtracted from the "clip", and the output level signal "Out" is calculated by multiplying the  
5 subtracted value with the amplification constant "gain". A key signal Fk2 as shown in Fig. 3C can be obtained by the limiter circuit which makes the output level signal "Out" 0 when "Out"<0 and makes "Out" 1.0 when "Out">1.0.

Next, the setting of a chroma key for deciding the  
10 extraction chroma conditions based on colors or both luminance and colors of the image will be explained. When the control panel 20 is provided with a two-dimensional chroma key setting device for two-dimensionally setting a color signal region of an extracted signal on a two-axis  
15 plane comprised of a U-axis of the chromaticity signal (B-Y) and a V-axis of the chromaticity signal (R-Y) by an input of boundary angles from a reference chromaticity signal axis, the chroma key for deciding the extraction chroma conditions based on the colors or both luminance  
20 and colors of the image is set by an operator operating the two-dimensional chroma key setting device. When the control panel 20 is provided with a three-dimensional chroma key setting device for three-dimensionally setting a color signal region of the extracted signal on a two-  
25 axis plane comprised of a U-axis of the chromaticity



signal (B-Y) and a V-axis of the chromaticity signal (R-Y) by an input of boundary angles from a reference chromaticity signal axis and furthermore the luminance Y of the color signal is also in accordance with a set distance from the reference position, the key is set by an operator operating the three-dimensional chroma key setting device.

When setting a color signal region of the extracted image from the two-dimensional chroma key setting device, by entering boundary angles  $\theta 1$  and  $\theta 2$  to the two-dimensional chroma key setting device, a boundary angle signal from the U-axis of the chromaticity signal (B-Y) is input on the two-axis plane comprised of the U-axis of the chromaticity signal (B-Y) and the V-axis of the chromaticity signal (R-Y) as shown in Fig. 6A and a color signal region 26 of the extracted image is selected two-dimensionally as shown in the shaded portion in Fig. 6A. The logic value of the chroma key signal becomes "1" in the color signal region 26, while becomes "0" in other regions. Also, when setting a color signal region of the extracted image from the three-dimensional chroma key setting device, by entering boundary angles in the same way as in the two-dimensional chroma key setting device and furthermore inputting the luminance Y of a color signal in accordance with the set distance from the

reference position, a color signal region 27 of, for example, a sphere having a radius of "r" from a central point "P", is selected on the three-dimensional coordinates including the luminance Y as shown in Fig.

- 5 6B. The logic value of the chroma key signal becomes "1" in the color signal region 27 and becomes "0" in regions other than that.

Similarly, lumi-key signals output from the plurality of lumi-key setting circuits 16a to 16m set  
10 with extraction luminance conditions based on the luminance of the image and chroma key signals output from the plurality of chroma key setting circuits 18a to 18n set with extraction chroma conditions based on colors or both luminance and colors of the image are respectively  
15 input to the NAM circuit 9 via the inversion circuits 17a to 17m and 19a to 19n. When extraction conditions overlapping with the input signals are set by the NAM circuit 9, the one having the higher level is selected and output. An output signal of the luminance and chroma  
20 condition setting circuit 7 is input to the wave-filtering and shaping circuit 8 for two-dimensional low pass filtering and signal shaping, and then input to the mask processing circuit 12 via the switch 11, which is normally switched to the terminal "t3" side when used.  
25 The mask processing circuit 12 is receives by input by

the operator a mask pattern signal from the mask pattern generator 14 for outputting a desired mask pattern signal. When the mask pattern signal is input, the output signal of the luminance and chroma condition setting circuit 7 processed in the wave-filtering and shaping circuit 8 is masked by the mask pattern signal. An output signal from the mask processing circuit 12 is input to the delay circuit 6 via the switch 13, which is normally switched to the terminal "t1" side when used.

10        On the other hand, for example, when image conversion processing of "posterization" for reducing the number of gradients of luminance data of the image and "solarization" for reducing the number of gradients of color data of the image are selected in the image  
15        conversion processing circuit 1 of the pre video modification unit 23 by an image conversion instruction in the instruction operation signal input from the control panel 20 by the operator, an image signal obtained by "posterization" and "solarization" of an  
20        input image signal from the input terminal "ti" is input to the delay circuit 2. At the same time, the input image signal from the input terminal "ti" is input to the delay circuit 3. Then, a delay of the output signal of the mask processing circuit 12 is adjusted in the delay circuit 6,  
25        a delay of the output signal of the image conversion

processing circuit 1 is adjusted in the delay circuit 2,  
and a delay of the input image signal is adjusted in the  
delay circuit 3. In the state where phases of the above  
match, the output signal of the image conversion

5 processing circuit 1 is input to the first input terminal  
of the mixer circuit 5, the input image signal is input  
to the second terminal of the mixer circuit 5, and the  
output signal of the mask processing signal 12 is input  
to the third input terminal of the mixer circuit 5.

10 The mixer circuit 5 designates a key signal output  
from the key signal generator 15 as "K", multiplies "K"  
with a difference signal of a conversion image signal "A"  
obtained by image conversion of the input image signal of  
the input terminal "ti" in the image conversion

15 processing circuit 1 and an image signal "B" which is the  
input image signal after passing through the delay  
circuit 3. Then, the image signal "B" is added to the  
calculated value. As a result, the mixer circuit 5

outputs a video signal "Out"  $((A-B) \cdot K + B)$ . As shown in

20 Fig. 2, the video signal is input to the transformation  
unit 24 from the pre video modification unit 23, however,  
when an image conversion instruction for reducing and  
moving a designated portion in the image to be processed  
is included in the instruction operation signal input

25 from the control panel by the operator, an address signal

for reduction and movement is supplied to the transformation unit 24 from the address generator 22 by an instruction signal from the system CPU 21. The transformation unit 24 performs processing for reduction and movement of the designated portion in the image. When jags etc. are generated at oblique line portions in the image, the jags are removed by the anti-alias filter. The processed image signal is then input to the post video modification unit 25.

10 In this case, when addition of a tail shaped moving locus or a star shaped moving locus or addition of background at the time of moving an image is selected for the output signal of the transformation unit 24 by a selecting operation by the operator, a tail shaped moving locus or a star shaped moving locus or a background is added in the post video modification unit 25. The special effect image finally obtained by the image processing is output from the post video modification unit 25.

As explained above, according to the present embodiment, image conversion processing of "posterization" and "solarization" for reducing the number of gradients of the image data, "mosaic" processing for dividing the image to blocks of uniform density, "mono" processing for making the image monochrome, or "contrast" processing for adjusting the

luminance differences of the image is selected in the image conversion processing circuit 1 by a selection operation by the operator. Extraction luminance conditions based on the luminance of the image and  
5 extraction chroma conditions based on the colors or both luminance and colors of the image are set. A shape and position of the mask pattern generated from the mask pattern generator 14 are selected in the luminance and chroma condition setting circuit 7. Then, the mixer  
10 circuit 5 processes a selected part of the image.

For a video signal, the transformation unit 24 performs various processing such as reduction and movement and removes the jags generated along with the processing. The post video modification unit 25 adds a  
15 tail shaped moving locus or a star shaped moving locus or adds a background to the image in accordance with need. Therefore, it is possible to give a visually unique effect in terms of luminance and colors to an image by an easy operation. Also, according to the present  
20 embodiment, even if the image moves, the image portion extracted by the set luminance and chroma conditions automatically moves in accordance with the movement of the image. Therefore, it is possible to prevent changes generated in the visual effects of the special effect  
25 image. Furthermore, it is possible to process only part

of a plurality of image parts having the same luminance and chroma conditions, for example, only one of two face images on a display screen, by easily adjusting the mask pattern from the mask pattern generator 14 to obtain a  
5 mask having a minimum area extending over a wide range.

Furthermore, it is possible to swiftly track movement and changes of the mask portion caused by movement of the image over a wide area with a high accuracy. Further, since the boundary region of the  
10 output signal from the luminance and chroma condition setting circuit 7 is broadened by the wave-filtering and shaping circuit 8 and the mask pattern from the mask pattern generator 14 is adjusted at a high accuracy, a portion desired to be processed can be completely covered  
15 when processing. For example, by broadening the boundary, it is possible to prevent incomplete mosaic processing, for example, leaving part of the face as it is when trying to give a mosaic effect to completely cover the face. By keeping the area of the mask portion to a  
20 minimum, it becomes possible to easily prepare a special effect image giving a clear and visually impressive effect excelling in luminance and color to a required region.

As explained above, the special effect image  
25 generation apparatus of the present embodiment comprises

an image conversion means for performing predetermined image conversion on the image; an extraction condition setting means for extracting from the above image an image satisfying a plurality of extraction conditions among luminance extraction conditions based on a luminance signal and/or chroma extraction conditions based on at least a color signal; a key signal output means for outputting a key signal for setting extraction conditions for the image based on the luminance extraction conditions and/or the chroma extraction conditions; and a mixer circuit for processing the image to convert the image to a special effect image based on a signal of the image, an output signal of the image conversion means, and the key signal.

More specifically, it further comprises a mask pattern generation means for outputting a mask pattern for masking a region not to be processed in the image and an image conversion setting and processing means for selecting and setting a type of image conversion to be performed on the image and making the image conversion means perform the selected and set image conversion on the image.

According to the above embodiment, the image conversion setting and processing means selects and sets a type of image conversion to be performed on the image



and performs the image conversion to the selected and set  
image, the extraction condition setting means sets  
luminance extraction conditions based on a luminance  
signal and chroma extraction conditions based on the  
5 luminance signal and color signals for the image, the  
region not to be processed in the image is masked by the  
mask pattern output from the mask pattern generation  
means, and a key signal of a portion to be extracted in  
the image which satisfies the predetermined luminance and  
10 chroma extraction conditions is output. Then, based the  
image signal, the output signal of the image conversion  
and setting processing means, and the key signal, the  
mixer circuit processes the image for the selected image  
conversion and extraction of image parts based on the  
15 predetermined luminance and chroma extraction conditions.  
Due to this, a predetermined image part in the image is  
extracted by distinctive luminance and chroma conditions  
and is converted to a special effect image.

As a result, it is possible to give a special effect  
20 to a predetermined part in an image and easily generate a  
high quality special effect image having a distinctive  
visual effect in luminance and colors can be easily  
generated. Furthermore, since the portion extracted from  
the image based on the predetermined luminance and chroma  
25 extraction conditions moves following movement of the

image, changes of visual effects of an image caused by movement of the image can be prevented.

In the special effect image generation apparatus of the present embodiment, the selection and setting of the type of image conversion in the image conversion setting and processing means, the setting of the luminance extraction conditions and/or chroma extraction conditions, and the setting and adjustment of a mask pattern generated by the mask pattern generation means can be freely and independently performed by the operator in accordance with the special effect image desired. As a result, the operator can accurately generate a special effect image of the desired high quality, and it becomes possible to suitably handle movement of the image by an easy operation of adjustment of the mask pattern.

Further, the special effect image generation apparatus of the present embodiment may be provided with a wave-filtering shaping means for filtering and shaping the output signal of the extraction condition setting means so as to broaden the luminance and chroma extraction region. Therefore, a high quality special effect image wherein boundary lines are smoothly set can be generated.

While the invention has been described with reference to specific embodiment chosen for purpose of

illustration, it should be apparent that numerous modification could be made thereto by those skilled in the art without departing from the basic concept and scope of the invention.

093490430  
093490430